



# Deco90

decompactor

**MECHANICAL GEARBOX**  
belt transmission



**RUNNING SPEED**




2.1 Km/h 1.1 Km/h  3.5 Km/h 2.5 Km/h 1.1 Km/h

**SEMI-PROFESSIONAL**




## Deco90

<b>ENGINE</b>	Briggs&Stratton 1000 Pxi 223 cc 4.3 kW Petrol
<b>STARTER</b>	recoil
<b>HANDLEBAR</b>	laterally and vertically adjustable
<b>TRANSMISSION</b>	gears and endless screw in oil bath and belts
<b>WORKING SYSTEM</b>	rotor 80 cm with 156 springs, 142 rpm brushes (x2) 90 cm dione oscillating one fixed, polypropylene bristles 95 mm independent engagement levers for rotor and brush
<b>ADJUSTMENTS</b>	spring rotor work depth 0 <-> 5 cm brush height precision adjustment 0 <-> 1 cm
<b>DRIVE WHEELS</b>	tyres, tractor profile with mechanical semi-differential (15x6.00-6")
<b>OTHER</b>	4 swivel wheels Ø17.5 cm limit stops for transport optional kit with 11 kg front ballast system
<b>NET WEIGHT</b>	143 kg
<b>DIMENSIONS</b>	105x168x95(h) cm

	<b>GR.WEIGHT</b> 172.5 KG
	<b>PACKAGING</b> 168X105X96(H) CM
	<b>PALLET</b> 168X105X192 (H) CM / Q* 2PCS



**PIVOTING WHEELS (X4)**  
with limit stop for transport



**TOOL COUPLING LEVER**  
sheet metal pressure with integrated safety system






**ROTOR COUPLING LEVER**  
with management of work depth levels



**SPRING ROTOR**  
independent activation  
80 cm - 142 rpm



**BRUSHES (X2)**  
of which oscillating front  
with independent coupling  
and work depth adjustment  
controls

-  **AS STANDARD**
-  **ACCESSORY**
-  **PATENTED**