

HAYMAKING

# M210

scythe mower

**MECHANICAL REDUCER**  
belt transmission



**RUNNING SPEED**




**AMATEUR**



## M210

<b>ENGINE</b>	<b>B&amp;S 450 and</b> 125 cc 1.8 kW Petrol	<b>B&amp;S 625 EXi</b> 150 cc 2.3 kW Petrol	<b>Euro 139.ohv</b> 139 cc 2.7 kW Petrol	<b>Euro R170.ohv</b> 173 cc 3.2 kW Petrol	<b>Honda GCV170</b> 166 cc 3.6 kW Petrol	<b>NEW</b> <b>EGOpower+ e-powered</b> 56 V 3.1 kW Electric
<b>STARTER</b>	recoil	recoil	recoil	recoil	recoil	electric
<b>HANDLEBAR</b>	laterally and vertically adjustable					
<b>TRANSMISSION</b>	endless screw in oil bath and belt					
<b>CUTTING SYSTEM</b>	double blade movement - oscillating upper and lower blade mowing bar: Eurosystems or ESM cutting width 87 cm					
<b>OTHER</b>	Eurosystems cutting bar with adjustable skids, adjustable cutting height 1.5 <-> 4.7 cm ESM cutting bar with optional adjustable skids, adjustable cutting height 1.5 <-> 4.7 cm					
<b>DRIVE WHEELS</b>	puncture proof, tractor profile 13x5.00-6"					
<b>NET WEIGHT</b>	50.5 kg	51 kg	50.5 kg	51.5 kg	51 kg	54 kg
<b>DIMENSIONS</b>	87x157x90(h) cm					

	<b>GR.WEIGHT</b>	54.5-59 KG
	<b>PACKAGING</b>	80X59X57(H) CM
	<b>PALLET</b>	80X120X240(H) CM / Q* 8PCS



**HANDLEBAR**  
vertically and laterally adjustable



**BI-LAMA MOVEMENT**  
two oscillating cutting blades 87 cm



**LEVERAGES**  
traction + tool coupling with integrated safety system



**DRIVEN WHEELS**  
tractor profile  
13x5.00-6"



**SNOW BLADE**  
85 cm  
adjustable  $\pm 30^\circ$



**AS STANDARD**



**ACCESSORY**



**PATENTED**