





Rtt2

• • • • • • • • • • • • • • •	• • • • • • • • • • • • • • • • •	••••••	• • • • • • • • • • • • • • • • • • • •	
ENGINE	Euro 182.ohv 182 cc 3.1 kW Petrol	Euro R210.ohv 212 cc 4.4 kW Petrol	B&S CR950 208 cc 4.0 kW Petrol	Honda GP160 163 cc 3.6 kW Petrol
• • • • • • • • • • • • • • •	• • • • • • • • • • • • • • • • • •		• • • • • • • • • • • • • • • • • • • •	
STARTER	recoil			
HANDLEBAR	vertically adjustable	vertically adjustable	vertically and laterally adjustable	vertically and laterally adjustable
TRANSMISSION	gears, chain in oil bath and double belt system 1 fixed milling speed, reverse			
ROTAVATOR	6 stars Ø32 cm - 16 riveted knives work width 50 cm 270 rpm			
OTHER	adjustable spur system for quick visual inspection of correct belt tensioning			
DRIVE WHEELS	tyres, tractor profile 13x5.00-6" with mechanical transport idler			
NET WEIGHT	65 kg	66 kg	67 kg	66.5 kg
DIMENSIONS	53X116.5X70(h) cm			

 GR.WEIGHT
 71-73 KG

 PACKAGING
 116,5X53X70(H) CM

 PALLET
 110X120X225(H) CM / Q* 6PCS



HANDLEBAR vertically and laterally adjustable* * B&S / Honda only



TOOL COUPLING LEVER with visual drive belt tensioning control system



ROTAVATOR riveted knives Ø32 cm 50 cm



DRIVEN WHEELS with mechanical semi-differential



SMALL ROTAVATOR cutter 32 cm iron wheels Ø35x5



e

RIDGING PLOW with fixed wings

